

# EDI – engine diagnostic system



## F1B5-S-X Cable



### Usage

The F1B5-S-X cable is used to connect the pressure sensor to the **EDI-Panel** and **EDI-Portable** devices. It has Fisher 103 and Lemo 1B5 connector tips. Silicone insulation of the cable assures its elasticity and resistance to high temperatures. The cable is characterized by excellent technical parameters.

### TECHNICAL SUPPORT

Training in operating **EDI** systems can be provided by us or our commercial partners.

### CONTACT

Address:  
UL. Okrężna 1  
81-822 Sopot  
Tel./Fax.:(+48 58) 341 16 61  
Mail:  
ultima@ultima-automatyka.pl  
Web:  
www.ultima-automatyka.pl  
www.ultima-automatics.com

### Technical parameters

Parameter	Description
Insulation material	Silicone, no fire propagation
Rated voltage	60 V
Fisher 103 connector protection degree	IP65
Lemo 1B5 connector protection degree	IP65 (after socket insertion)
Work environment temperature	-60°C...220°C
Work environment relative humidity	20%...95%
Lenght (F1B5-S-3)	3 m
Lenght (F1B5-S-7)	7 m
Catalogue number (F1B5-S-3)	16-03-0102-01
Catalogue number (F1B5-S-7)	16-03-0102-02